

MATERIAL SAFETY DATA SHEET (MSDS)

THIS MSDS IS EFFECTIVE JANUARY 1, 2018 AND SUPERSEDES ALL PREVIOUSLY ISSUED SAFETY DATA SHEETS.

SECTION I (IDENTIFICATION)

Manufacturer/ Processor/Importer:	Eagle Alloys Ltd. Emergency Tel No (780) 481 8082
Address:	10077 - 166 Street Edmonton Alberta T5P 4Y1
Product Name:	Eagle 635
Classification:	Covered Arc Welding for SMAW

SECTION II (HAZARDOUS INGREDIENTS/IDENTITY INFORMATION)

IMPORTANT: This section covers the materials of which the products are manufactured. The fumes and gases produced during normal use of the product are covered in Section V. The term "Hazardous" in "Hazardous" should be interpreted as a term required and defined in OSHA Hazard Communication Standard 29CFR 1910-1200 and it does not necessarily imply the existence of hazard.

INGREDIENTS	CAS NUMBER	PERCENT RANGE	OSHA PEL mg/M ³	ACGIH-TLV mg/M ³	Carcinogenicity
Iron	7439-89-6	40 - 70	10 (as Fe)	5 (as Fe)	NO
Calcium Carbonate	1317-65-3	1 - 5	5	10	NO
Manganese	7439-96-5	0.1 - 1	5 (ceiling)	.02	YES
Sodium Silicate	1344-09-8	1 - 5	N/A	5	NO
Potassium Silicate	1312-76-1	1 - 5	N/A	5	NO
Calcium Fluoride	7789-75-5	1 - 5	2.5 (as F)	2.5 (as F)	NO
Chromium	7440-47-3	30 - 60	.05	.05	YES
Carbon	7440-44-0	3 - 7	2.5	2	NO
Silicon Dioxide	14808-60-7	0.1 - 1	.01	0.1	NO
Titanium Dioxide	13463-67-7	1 - 5	5	10	NO

SECTION III (PHYSICAL DATA) Not Applicable

SECTION IV (FIRE AND EXPLOSION HAZARD DATA)

Non-Flammable - Welding arc and sparks can ignite combustibles. Refer to American National Standard Z49.1 for fire prevention during welding.

SECTION V (REACTIVITY DATA)

Welding fumes cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedures and electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which worker's may be exposed include: coatings on the metal being welded (such as paint, plating or galvanization), number of welds and volume of work area, quality and amount of ventilation, position of weldor's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the electrode is consumed, the fume and gas decomposition products are different in percent and form from the ingredients listed in Section II. Fume and gas decomposition products, not the ingredients in the electrode, are important. Decomposition products include those originating from the volatilization, reaction, or oxidation of the materials shown in Section II plus those from the base metal, coating, etc. as noted above. These components are virtually always present as complex compounds and not as metals (Characterization of Arc Welding Fume: American Welding Society).

SECTION V (REACTIVITY DATA) CON'T

Reasonably expected fume constituents would include fluorides and complex oxides of iron, chromium, and silicon. Fume limit for Cr VI ($0,05\text{mg}/\text{M}^3$) may be reached before limit of $5\text{ mg}/\text{M}^3$ for general welding fumes is reached. Monitor Cr VI level. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc in TIG welding. One recommended way to determine the composition and quantity of fumes and gases to which worker's are exposed is to take an air sample inside the weldor's helmet, if worn, or in the worker's breathing zone. ANSI/AWS FL,1 available from the American Welding Society. P.O. Box 351040, Miami, FL 33135.

SECTION VI (HEALTH HAZARD DATA)

Threshold Limit Value: The ACGIH recommended general limit for welding fume NOC (Not Otherwise Classified) is $5\text{mg}/\text{M}^3$. The ACGIH 1984-85 preface states: "The TLV-TWA should be used as guides in the control of health hazards and should not be used as firm lines between safe and dangerous concentrations." See Section V for specific fume constituents that may modify this TLV.

Effects of Overexposure: FUMES AND GASES can be dangerous to your health. Primary route of exposure is inhalation of fumes. Preexisting respiratory or allergic conditions may be aggravated in some individuals. SHORT-TERM (ACUTE) OVEREXPOSURE to welding fumes may result in discomfort such as: dizziness, nausea, or dryness or irritation of nose, throat, or eyes. LONG-TERM (CHRONIC) OVEREXPOSURE may lead to siderosis (iron deposits in the lungs) and is believed by some investigators to affect pulmonary function. ARC RAYS can injure eyes and burn skin. ELECTRIC SHOCK can kill. See Section VII.

Emergency & First Aid: Call for medical aid. Employ first aid techniques recommended by the Canadian Red Cross.

Carcinogenicity When Present	NTP? Cr	I Arc Monographs Cr	OSHA Regulated Cr
---------------------------------	------------	------------------------	----------------------

SECTION VII (PRECAUTION FOR SAFE HANDLING AND USE/APPLICABLE CONTROL MEASURES)

Read and understand the manufacture's instructions and the precautionary label on this product. See American National Standard Z-49.1, Safety in Welding and cutting, published by the American Welding Society, P.O. Box 351040, Miami, FL 33135 and OSHA Publication 2206 (29CFR 1910), US Government Printing Office, Washington D.C. 20402 for more detail on the following:

Ventilation: Use enough ventilation, local exhaust at the arc, or both to keep the fumes and gases below the TLV'S in the worker's breathing zone and the general area. Train the weldor to keep his head out of the fumes.

Respiratory Protection: Use respirable fume or air supplies respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below TLV.

Eye Protection: Wear helmet or use face shield with filter lens. As a rule of thumb, Start with a shade darker to see weld zone. Then go to the next lighter shade that gives sufficient view of the weld zone. Provide screens and flash goggles, to shield others.

Protective Clothing: Wear head, hand and body protection that help to prevent injury from radiation, sparks and electrical shock. See ANSI Z-49.1. At a minimum, this includes weldor's gloves and a protective face shield and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the weldor not to touch live electrical parts and to insulate himself from work and ground.

Waste: Dispose of any grinding dust or waste residues in accordance with EPA or local regulations.

The information in this MSDS was obtained from sources we believe are reliable. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods or handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons we do not assume responsibility and expressly disclaim liability or loss, damage or expense arising from it or in any way connected with the handling, storage, use or disposal of the product.